

Specifications

Compound

466196

maharam

Application

Seating

Characteristics

Content: 100% Polyurethane

Finish: None

Backing: Polyester

Width: 54" (137cm)

Bolt Size: 30 yards (27 m)

Weight: 17.7 oz/ly (549 gr/lm)

Country of Origin: Taiwan

Price

Contact your sales representative for pricing.

Maintenance

W/B-Clean with water-based cleanser or diluted household bleach.



Testing

Abrasion: ASTM D4966, 100,000 cycles Martindale

Note: Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan.

Multiple factors affect fabric durability and appearance retention.

Flammability: AS/NZS 3837 Unadhered

ASTM E 84 Unadhered*

BS 5852 Crib 5*

CAL 117-2013

EN 1021-1*

EN 1021-2*

GB/T 17591*

ISO 5660 Unadhered

*passes with additional treatment

Lightfastness: AATCC 16E, 500+ hours



Specifications
Compound
466196

maharam

Environmental


Greenguard Gold Certified
LBC Red List Free
REACH Compliant
PFAS Free
DMF Free

Warranty

5 years.

© 2013 Maharam


Complete product information at maharam.com
800.645.3943




001 Quartz




002 Mirage




003 Weathered




004 Cliff



005 Espresso



006 Smolder



007 Blaze



008 Mandarin




009 Maple




010 Perennial




011 Mountainside




012 Tundra




013 Manatee




014 Marine




015 Twilight




016 Shelter



017 Vessel



018 Smoke



019 Fog