



### APPLICATION

Upholstery/decoration

### WIDTH

140 cm

### WEIGHT

700 GR/MTL

### TARIFF CODE

58013700

### DRY CLEANING DIMENSIONAL STABILITY

ISO 3175: Trama 0 % - weft, Ordito 0 % - warp

### MACHINE WASHING 60° DIMENSIONAL STABILITY

ISO 3175: Trama 0,53 % - weft, Ordito 0,67 % - warp

### COLOUR FASTNESS TO RUBBING

Dry UNI EN ISO 105 X 12: 4/5 TRAMA / WEFT

Wet UNI EN ISO 105 X 12: 4 TRAMA / WEFT

### LIGHT FASTNESS

UNI EN ISO 105B02: 5

### PILING

ISO 12945-2:2000: 5

### TEAR STRENGTH

UNI EN ISO 13937-3:2000: 27,48 N ORDITO / WARP, 49,22 N TRAMA / WEFT

### TENSILE STRENGTH

UNI EN ISO 13934-1: 1135,63 N ORDITO /WARP Elongation 20,22%  
972,43 N TRAMA / WEFT Elongation 24,90%

### SEAM SLIPPAGE

UNI EN ISO 13936-2: 2 ORDITO /WARP, 2 TRAMA / WEFT

### RESISTANCE TO ABRASION / MARTINDALE

ISO 12947-2: >100,000 GIRI End point at rubs

### FIRE TREATMENT

**Cigarette and Match EN 1021 1 and 2:**

Yes, but needs treatment (30m MOQ)

**BS 5852 Crib5:**

No (not possible)

**CAL 117:**

Yes, but needs treatment (30m MOQ)

### COMPOSITION

92% PES, 5% CO, 3% LA

The overmentioned numbers represent average values communicated in good faith, but they cannot be considered as a contract document. Consider if the application is appropriate before choosing this fabric, as the product cannot be held responsible when improperly used. There may be slight colour variations between batches.

